

Casca de sudura auto-intunecare DIN 9-13 Gr 90x35 RD-WH05

Numar articol: **138345**

Cod de bare: **3800972027848**

- ✓ Controlul opacitatii
- ✓ Oprire si pornire complet automata
- ✓ Celula solara si baterie Li-Ion
- ✓ Modern design



TECHNICAL FEATURES

Parameter	Measure Unit	Value
Protectie UV/IR (DIN)	DIN	16
Timp de adaptare lumina/intuneric (sec)	sec	0.2 - 0.5
Material		PP
Dimensiune (mm)	mm	110x90
Ambalare (buc.)	buc.	1
Senzor		1
Gradul de inchidere (DIN)	DIN	9-13
Tensiune nominala		Celule solare si baterie Li-Ion
In conformitate cu		CE EN175 EN379
Pornire si oprire		In mod automat
Timp de comutare (sec)	sec	1/25000
Domeniu sudura TIG (amps/DC; amps/AC)	amps/DC; amps/AC	≥ 35; ≥ 15
Umbrire constanta (DIN)	DIN	4
Dimensiuni filtru (mm)	mm	110x90x9
Controlul sensibilitatii		Reglajul partii interioare de la mic la mare

LOGISTICS INFORMATION

Tipul ambalajului	Cantitate	Inaltime Lungime Inaltime	Volum	Net Brut Tara	Cod de bare
buc	1 buc	27 x 24 x 28 cm	0.01814 m3	0.7350 - 0.8167 - 0.0817 kg	3800972027848
bax	6 buc	29 x 74 x 56 cm	0.12018 m3	4.9000 - 4.9000 - 0.0000 kg	38009720278488